NSN 5305-00-489-0035

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-489-0035 **Thread Class:** 2a **Thread Direction:** Right-hand Fastener Length: Between 0.219 inches and 0.250 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Primary Washer Outside Diameter:** Between 0.220 inches and 0.230 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** 0.014 inches Material: Steel comp 302 or steel comp 303 or steel comp 304 **Material Specification:** Aisi assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish no. E300, type 1 military specification 1st treatment response or mil-f-14072, finish no. E300, type 2 military specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-00-489-0035

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.