

View Online at <https://aerobasegroup.com/nsn/5305-00-489-1375>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.250 inches

Fastener Length:

Between 2.210 inches and 2.250 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.550 inches and 0.562 inches

Head Height:

Between 0.368 inches and 0.375 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.375 inches

Width Across Flats:

Between 0.312 inches and 0.316 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

Material Specification:

66 federal standard all material responses or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or 66 federal standard 5th material response or astm a493 assn standard 6th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0