

View Online at <https://aerobasegroup.com/nsn/5305-00-489-1406>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.284 inches and 0.324 inches

**Fastener Length:**

Between 0.344 inches and 0.375 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.249 inches and 0.279 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Stainless steel

**Screw Material Specification:**

Qq-s-763 300 series federal specification single material response or 66 300 series federal standard single material response or comp 16-8 assn standard single material response

**Screw Surface Treatment:**

Oxide

**Screw Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Special Features:**

To be threaded to base of head

**Thread Series Designator:**

Unc

**Specification Or Standard:**

3 type and 3c style

**Departure From Cited Designator:**

As modified by thd length and finish

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-c-13924 spec.