

View Online at <https://aerobasegroup.com/nsn/5305-00-489-8826>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.559 inches and 0.587 inches

Fastener Length:

Between 0.615 inches and 0.635 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Washer Quantity:

2

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Secondary Washer Relationship To Primary Washer:

Not identical

Secondary Washer Style:

Flat

Primary Washer Outside Diameter:

0.209 inches

Secondary Washer Outside Diameter:

0.250 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

Between 0.025 inches and 0.031 inches

Secondary Washer Material Thickness:

Between 0.017 inches and 0.031 inches

Special Features:

Lock washer rockwell c scale 45 to 53

Material:

Steel comp 1020 secondary washer or steel comp 1025 secondary washer or steel secondary washer

Material Specification:

Astma576 assn standard all material responses primary washer

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7952 spec.