

View Online at <https://aerobasegroup.com/nsn/5305-00-489-8826>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.559 inches and 0.587 inches

**Fastener Length:**

Between 0.615 inches and 0.635 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**Washer Quantity:**

2

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Secondary Washer Relationship To Primary Washer:**

Not identical

**Secondary Washer Style:**

Flat

**Primary Washer Outside Diameter:**

0.209 inches

**Secondary Washer Outside Diameter:**

0.250 inches

**Primary Washer Style:**

Split helical ring

**Primary Washer Material Thickness:**

Between 0.025 inches and 0.031 inches

**Secondary Washer Material Thickness:**

Between 0.017 inches and 0.031 inches

**Special Features:**

Lock washer rockwell c scale 45 to 53

**Material:**

Steel comp 1020 secondary washer or steel comp 1025 secondary washer or steel secondary washer

**Material Specification:**

Astma576 assn standard all material responses primary washer

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-7952 spec.