## NSN 5305-00-490-1749



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-490-1749 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.324 inches and 0.428 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.348 inches and 0.385 inches **Locking Feature:** Pellet or strip **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel or plastic **Screw Material Specification:** 66 federal standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard: Departure From Cited Designator:** 

3 type and 3c style

Departure From Cited Designator
As mod by matl and locking feature

Shelf Life:

N/a

Unit Of Measure:

--

## NSN 5305-00-490-1749

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0