NSN 5305-00-490-4580

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-490-4580 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.183 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.155 inches and 0.167 inches **Head Height:** Between 0.053 inches and 0.062 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 316 **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:** Unc **Specification Data:** 96906-ms51957 government standard and 06481-950726l/inactive/ manufacturers specification control **Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A500d0

NSN 5305-00-490-4580

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.