## NSN 5305-00-490-6523

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-490-6523 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.220 inches and 0.341 inches **Fastener Length:** Between 0.739 inches and 0.769 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.363 inches and 0.395 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp 4140 or steel comp 8740 or steel comp 4130 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-00-490-6523

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0