## NSN 5305-00-491-1374

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-491-1374 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.260 inches and 0.310 inches **Fastener Length:** Between 0.560 inches and 0.580 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.253 inches and 0.267 inches **Head Height:** Between 0.080 inches and 0.100 inches **Shoulder Diameter:** 0.169 inches first shoulder and 0.175 inches first shoulder **Shoulder Length:** 0.195 inches first shoulder and 0.205 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder **Special Features:** Third shoulder 0.169 in. Min dia. By 0.175 in. Maximum dia, 0.023 in. Min by 0.026 in. Maximum Ig Material: Steel comp 303 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5305-00-491-1374** Shoulder Screw - Page 2 of 2



Fiig:

A003b0