NSN 5305-00-491-1377



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-491-1377 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.340 inches and 0.350 inches **Fastener Length:** Between 0.850 inches and 0.870 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches **Shoulder Diameter:** 0.135 inches first shoulder and 0.141 inches first shoulder **Shoulder Length:** 0.418 inches first shoulder and 0.428 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Shoulder Shape:** Round all shoulders **Special Features:** Third shoulder 0.135 in. Min by 0.141 in. Maximum dia, 0.028 in, min by 0.038 in. Maximum Ig Material: Steel comp 303 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life: N/a Unit Of Measure: --Demilitarization: No

NSN 5305-00-491-1377 Shoulder Screw - Page 2 of 2



Fiig:

A003b0