NSN 5305-00-492-2207

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-492-2207

view Offilite at https://aerobasegroup.com/htst//3303-00-432-2207
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.297 inches and 0.391 inches
Fastener Length:
Between 0.359 inches and 0.391 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.185 inches and 0.190 inches
Head Height:
Between 0.303 inches and 0.312 inches
Locking Feature:
Strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.159 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Material:
Steel fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416, type 2 class 2 federal specification single treatment response fastener
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a

NSN 5305-00-492-2207

Socket Head Cap Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0