# NSN 5305-00-492-2371

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-492-2371



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 1.468 inches and 1.580 inches

#### Fastener Length:

Between 1.563 inches and 1.625 inches

#### Head Style:

Flat countersunk

## Head Diameter:

Between 0.183 inches and 0.225 inches

## Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.112 inches

## Thready Qty Per Inch (tpi):

40

## Min. Tensile Strength (psi):

125000 pounds per square inch

## Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Product Name:**

Navy special project

#### Screw Material:

Steel comp 4037 or steel comp 8630

## Screw Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response

#### Screw Surface Treatment:

Cadmium and chromate

## Screw Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

## Thread Series Designator:

Unjc

## **Specification Data:**

80205-nas514 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5305-00-492-2371

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

