NSN 5305-00-492-3064

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-492-3064 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.812 inches **Fastener Length:** Between 0.906 inches and 0.940 inches **Head Style:** Flat countersunk **Head Diameter:** 0.390 inches Washer Quantity: **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 100.0 degrees **Primary Washer Outside Diameter:** Between 0.640 inches and 0.660 inches **Primary Washer Style:** Spring tension **Primary Washer Material Thickness:** Between 0.015 inches and 0.021 inches Material: Steel comp 8740 fastener **Material Specification:** Sae assn standard single material response primary washer **Surface Treatment:** Cadmium primary washer and chromate primary washer **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response primary washer **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-492-3064

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.