

View Online at <https://aerobasegroup.com/nsn/5305-00-492-9071>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.564 inches and 0.667 inches

**Fastener Length:**

Between 0.719 inches and 0.750 inches

**Head Style:**

Oval countersunk

**Head Diameter:**

Between 0.333 inches and 0.385 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

62000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Aluminum alloy 2024

**Screw Material Specification:**

Qq-a-225/6 federal specification single material response

**Screw Surface Treatment:**

Anodize and paint

**Screw Surface Treatment Specification:**

Mil-c-5541 military specification 1st treatment response

**Special Features:**

Painted area cream color no. 27778, fed-std-595

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-c-5541 spec.