## NSN 5305-00-494-1953

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-494-1953 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.235 inches and 0.265 inches **Fastener Length:** Between 0.422 inches and 0.452 inches **Head Style:** Watertight **Head Diameter:** 0.284 inches **Head Height:** 0.075 inches **First Diameter From Head:** 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.157 inches and 0.217 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity: Special Features:** Furnished with one o-ring seal and one polytetrafluoroethylene shim Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-494-1953

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0