NSN 5305-00-494-1974

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-494-1974 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.177 inches and 0.197 inches **Fastener Length:** Between 0.427 inches and 0.457 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.238 inches and 0.279 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.230 inches and 0.280 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-494-1974

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0