NSN 5305-00-494-5678

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-494-5678

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.475 inches and 0.557 inches
Fastener Length:
Between 0.939 inches and 0.949 inches
Head Style:
Flat chamfer
Head Diameter:
0.350 inches
Head Height:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 0.392 inches and 0.402 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
40.0 microinches grip
Material:
Steel comp 4130 or steel comp 4140 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-00-494-5678

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0