

View Online at <https://aerobasegroup.com/nsn/5305-00-494-7240>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.750 inches

**Fastener Length:**

Between 1.359 inches and 1.391 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.457 inches and 0.469 inches

**Head Height:**

Between 0.306 inches and 0.312 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.312 inches

**Width Across Flats:**

0.250 inches

**Thready Qty Per Inch (tpi):**

18

**Hardness Rating:**

36.0 rockwell c and 43.0 rockwell c

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

**Test Data Document:**

81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**