## NSN 5305-00-494-8008

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-494-8008 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.485 inches **Fastener Length:** 0.485 inches **Head Style:** Fillister **Head Diameter:** Between 0.389 inches and 0.414 inches **Head Height:** Between 0.219 inches and 0.237 inches **Hole Diameter:** 0.064 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Hole Quantity:** 2 Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch **Screw Material:** Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 **Screw Material Specification:** Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response **Screw Surface Treatment:** Cadmium **Head Hole Configuration Style:** Round **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-00-494-8008

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6758 spec.