NSN 5305-00-498-3186

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-498-3186 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.455 inches and 0.565 inches **Fastener Length:** 0.900 inches **Head Style:** Flat countersunk **Head Diameter:** 0.875 inches **Shoulder Diameter:** 0.622 inches first shoulder and 0.623 inches first shoulder **Shoulder Length:** 0.195 inches first shoulder and 0.205 inches first shoulder **Internal Drive Style:** Torque **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 150000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel **Material Specification:** Mil-s-5626com+4140condc military specification single material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-498-3186

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626com spec.