## NSN 5305-00-498-6801

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-498-6801 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.531 inches and 0.594 inches **Fastener Length:** Between 0.922 inches and 0.953 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.079 inches and 0.089 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.359 inches and 0.391 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 416 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 171, finish no. 5.4.1 military standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Deminiani

No

## NSN 5305-00-498-6801

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0