Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-498-6804

Ba Thread Direction: Right-hand Thread Length: Between 0.139 inches and 0.165 inches Fasteer Length: Between 0.159 inches and 0.165 inches Head Skyle: Flat chamfer Between 0.050 inches and 0.060 inches Head Directer: Between 0.057 inches and 0.060 inches Head Directer: 0.060 inches Thread Directer: 0.050 inches Thread Directer: 0.050 inches Mith Across Flats: 0.050 inches Thready Chy Per Inch (tpl): 0.050 onches Minum Yield Strength Minum Yield Strength: 0.050 onches bearing surface of head Matriai: 0.50 oncickes bearing surface of head Matriai: 0.50 oncickes bearing surface of head Matriai: 0.50 oncickes bearing surface of	Thread Class:
Tread Direction: Right-hand Thread Length: Between 0.134 inches and 0.165 inches Faster Length: Between 0.159 inches and 0.165 inches Head Style: Flat chamfer Head Dimeter: Between 0.091 inches and 0.096 inches Head Proje: Between 0.097 inches and 0.096 inches Head Dimeter: Between 0.057 inches and 0.060 inches Herad Dirve Style: Herad Dirve Style: Herad Dirve Style: Herad Dirve Style: Ox60 Inches Muthards Ration: 0.050 Inches With Across Flats: 0.050 Inches Mintoms Rating: 0.050 Ourds per square inch Harders Rating: 0.000 pounds per square inch Harders Rating: 0.000 pounds per square inch Mutrares Flats: 0.000 pounds per square inch Mutrares Rating: 0.000 pounds per square inch Mutrares Rating: 0.000 pounds per square inch Mutrares Rating: 0.000 pounds per square inch </td <td></td>	
Righ-hand Horead Length: Between 0.134 inches and 0.165 inches Falser Length: Between 0.159 inches and 0.165 inches Had Skyle: Bit chamfer Head Skyle: Between 0.091 inches and 0.096 inches Head Right: Between 0.091 inches and 0.096 inches Head Right: Between 0.097 inches and 0.096 inches Head Right: Between 0.097 inches and 0.096 inches Head Dianeter: Between 0.097 inches and 0.096 inches Head Dianeter: 0.090 inches With Across Flats: 0.090 inches With Across Flats: 0.090 inches Minerasi Strength (psi): 0.000 pounds per square inch Hardness Rating: 0.000 pounds per square inch Minimum Yield Strength: 0.000 pounds per square inch Minimum Yield Strength: 0.000 pounds per square inch Strence Flats: 0.010 pounds per square inch Strence Flats: 0.020 pounds per square inch Betwewewewewewewewewewewewewewewewewewew	
Tread Length: Between 0.134 inches and 0.165 inches Fastener Length: Between 0.159 inches and 0.165 inches Head Style: Flat chamfer Head Diameter: Between 0.057 inches and 0.066 inches Head Diameter: Between 0.057 inches and 0.060 inches Head Diameter: Between 0.057 inches and 0.060 inches Head Diameter: Between 0.057 inches and 0.060 inches Head Diameter: 0.060 inches Meter Diameter 0.060 inches With Across Flats: 0.060 inches Minter Strengt (psi): 800 opounds per square inch Hardness Rating: 80.0 rockwell b Minium Yield Strength: 90.0 rounds per square inch Marce 90.0 rounds per square inch 90.0 rounds per square inch 90.0 rounds per square inch	
Between 0.134 inches and 0.165 inches Fastener Length: Between 0.159 inches and 0.165 inches Head Style: Flat chamfer Between 0.010 inches and 0.096 inches Between 0.057 inches and 0.096 inches Between 0.057 inches and 0.060 inches Internal Drive Style: Between 0.057 inches and 0.060 inches Internal Drive Style: Between 0.057 inches and 0.060 inches Internal Drive Style: Between 0.057 inches and 0.060 inches Internal Drive Style: Between 0.057 inches and 0.060 inches Internal Drive Style: Between 0.057 inches and 0.060 inches Internal Drive Style: Between 0.057 inches and 0.060 inches Micharcoss Flats: 0.050 inches With Across Flats: 0.050 inches Minternst (pls): 8000 pounds per square inch Hardness Rating: 80.07 ockwell b Mintern Yield Strength: 80.07 ockwell b Mintern Yield Strength: 80.07 ockwell b Strater Flatsh: 80.07 ockmols bearing surface of head	-
Fasteer Length: Between 0.159 inches and 0.165 inches Head Siyle: Flat chamfer Head Diameter: Between 0.091 inches and 0.096 inches Head Dight: Between 0.091 inches and 0.096 inches Head Dight: Between 0.097 inches and 0.060 inches Head Dight: Between 0.057 inches and 0.060 inches Hernal Drive Skyle: Hexagon Ox60 inches Vidth Across Flats: 0.050 inches Vidth Across Flats: 0.050 inches Min-Tensile Strength (psi): 8000 pounds per square inch Burdinum Yield Strength: 0.000 pounds per square inch Minimum Yield Strength: 0.000 pounds per square inch Suffere Finish: 0.000 pounds per square inch Suffere Finish: 1000 pounds per square inch Suffere Finish: 10100 pounds per square inch Suffere Finish: 10200 pounds per square inch Suffere Finish: 10210000000000000000000000000000000000	
Between 0.159 inches and 0.165 inches Flat chamfer Between 0.091 inches and 0.096 inches Between 0.091 inches and 0.096 inches Between 0.091 inches and 0.096 inches Between 0.057 inches and 0.060 inches Between 0.057 inches 300.060 inches 0.060 inches With Across Flats: 0.050 inches Boto inches Boto inches Boto inches Boto inches (psi): 8000 pounds per square inch Boto inches Boto inches berging undice of head Minimum Yield Strength: 8000 pounds per square inch Boto inches berging undice of head Boto inches berging undice of head Boto inches berging undice of head Boto inches belong 304 or steel comp 306 or steel comp 316 or steel comp 384 or steel comp and - Boto inches berginglication <td< td=""><td></td></td<>	
Head Style: Flac chamfer Head Diameter: Between 0.091 inches and 0.096 inches Head Height: Between 0.057 inches and 0.060 inches Head Nameter: Internal Drive Style: Heagon Thread Diameter: 0.060 inches Vidth Across Flats: 0.050 inches Thready Style: 0.050 inches Mith Across Flats: 0.050 inches Thready Style: 0.050 inches Mith Across Flats: 0.050 inches Mither Style: 0.050 inches Mither Style: 0.050 inches Mither Stating: 0.050 inches Mither Stating: 0.050 inches Mither Stating: 0.050 inches Stating Strength (psi): Storokwell b Minimum Yield Strength: 0.050 inches searing surface of head Marcia: Storokmels searing surface of head Miteria: Storokmel Steree (Storet Storet Storet Storet Storet Storet Storet Storet Sto	
Flat chamfer Head Diameter: Between 0.091 inches and 0.096 inches Head Height: Detween 0.057 inches and 0.060 inches Internal Drive Style: Heagon Thread Diameter: 0.060 inches Width Across Flats: 0.050 inches Thread Varper Inch (tpi): 80 Min Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 8000 pounds per square inch Surface Finish: 80.0 rockwell b Minimum Yield Strength: 80.0 rockwell b Surface Finish: 80.1 rockwell b Surface Finish: 80.2 rockwell b Surface Finish: 80.3 rocrionehes bearing surface of head Materiai: Surface Treatment: Pasivate Pasivate Pasivate Surface Treatment Specification: Pasivate	
Head Diameter: Between 0.091 inches and 0.096 inches Head Height: Between 0.057 inches and 0.060 inches Internal Drive Style: Hexagon Thread Diameter: 0.060 inches Witht Across Flats: 0.050 inches Motion (pp) 0.050 inches Mitht Across Flats: 0.050 inches Motion S Mitht Across Flats: 0.050 inches Motion S Motion S Motion S Motion S Motion S Motion S Solo inches Solo inches Motion S Motion S Motion S Solo inches Solo inches Boolo pounds per square inch Motion Meld Strength: Solo Opounds per square inch Surface Finish: Gold pounds per square inch Motioni Solo consteel comp 304 or steel comp 305 or steel comp 316 or steel comp 346 or steel comp a76 Surface Treatment: Pasivate Dapolici	-
Between 0.057 inches and 0.096 inches Head Heigh: Between 0.057 inches and 0.060 inches Internal Drive Style: Hexagon Thread Diameter: 0.060 inches Vidth Across Flats: 0.050 inches Vidth Across Flats: 0.050 inches Thready dty Per Inch (tpl): 80 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Ninimum Yield Strength: 90000 pounds per square inch Surface Finish: 90000 pounds per square inch Surface Treatment: 90000 pounds per square inch 90000 pounds per squa	
Head Height:Between 0.057 Inches and 0.060 InchesInternal Drive Style:HexagonThread Diameter:0.060 InchesWith Across Flats:0.050 InchesThready Qty Per Inch (pj):80Min. Tensile Strength (psi):8000 pounds per square InchHordenss Rating:80.00 rockwell bMinimum Yield Strength:8000 pounds per square InchSufface Finish:80.00 pounds per square InchSufface Finish:80.00 pounds per square InchSurface Finish:80.10 rockwell bSurface Finish:81.20 rockwell bSurface Finish:82.30 role steel comp 304 or steel comp 305 or steel comp 384 or steel comp xm.71Surface Treatment:PassivatePassivateBourde Streatentent response	
Between 0.057 inches and 0.060 inches Internal Drive Style: Hexagon Thread Diameter: 0.060 inches Width Across Flats: 0.050 inches Thready Qty Per Inch (tpi): 80 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Barface Finish: 63.0 microinches bearing surface of head Material: Streace Finish: 63.0 microinches bearing surface of head Material: Streace Treatment: Passivate Passivate Parsotate	
Internal Drive Style:HexagonThread Diameter:0.060 inchesWidth Across Flats:0.050 inchesThready Qty Per Inch (tpi):80Min. Tensile Strength (psi):8000 pounds per square inchHardness Rating:80.01 orckwell bMinimum Yield Strength:9000 pounds per square inch9019029030 pounds per square inch9049049059059059069069079079089099099099099000	-
HexagonThread Diameter:0.060 inchesWidth Across Flats:0.050 inchesThready Qty Per Inch (tpi):80Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell bMinimum Yield Strength:30000 pounds per square inchSufface Finish:80.0 rockwell bSufface Finish:81.0 rock per square inchSufface Finish:82.0 rock per square inchSufface Finish:83.0 rock per square inchSufface Tinish:83.0 rock per square inchSufface Treatment:94.0 rock per square inch95.0 rock per square inch95.0 rock per square inch96.0 rock per square inch96.0 rock per square inch97.0 rock per square inch98.0 rock per square inch98.0 rock per square inch99.0 rock per square inch99.0 rock per square inch90.0 rock per square inch<	
Thread Diameter:0.060 inchesWidth Across Flats:0.050 inchesThready Qty Per Inch (tpi):80Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell bMinimum Yield Strength:30000 pounds per square inchSufface Finish:63.0 microinches bearing surface of headMaterial:Stel comp 302 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7Sufface Treatment:PassivateGurqp-35 federal specification single treatment response	-
0.060 inchesWidth Across Flats:0.050 inchesThready Qty Per Inch (tpi):80Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell bMinimum Yield Strength:30000 pounds per square inchSurface Finish:63.0 microinches bearing surface of headMetrial:Stel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7Surface Treatment:PassivateCurface Treatment Specification:Curp-35 federal specification single treatment response	
Width Across Flats:0.050 inchesThready Cty Per Inch (tpi):80Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell bMinimum Yield Strength:30000 pounds per square inchSurface Finish:63.0 microinches bearing surface of headMaterial:Stel comp 302 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7Surface Treatment:PassivateGurp-St fiederal specification:Cup-S5 fiederal specification single treatment response	
0.050 inches Thready Qty Per Inch (tpi): 80 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimun Yield Strength: 80000 pounds per square inch Surface Finish: 81.0 microinches bearing surface of head Material: 81.2 Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 384 or steel comp xm-7 Surface Treatment: Passivate Passivate Qu-p-35 federal specification single treatment response	
Thready Qty Per Inch (tpi):80Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell bMinimum Yield Strength:30000 pounds per square inchSurface Finish:63.0 microinches bearing surface of headMaterial:Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 384 or steel comp xm-7Surface Treatment:PassivateSurface Treatment Specification:Qr.p-35 federal specification single treatment response	Width Across Flats:
80Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.01 rockwell bMinimum Yield Strength:30000 pounds per square inchSurface Finish:63.01 nicroinches bearing surface of headMaterial:Stel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7Surface Treatment:PassivateGurp-35 federal specification single treatment response	
Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell bMinimum Yield Strength:30000 pounds per square inchSurface Finish:63.0 microinches bearing surface of headMaterial:Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7PassivatePassivateSurface Treatment:PassivateSurface Treatment Specification:Qr-p-35 federal specification single treatment response	Thready Qty Per Inch (tpi):
80000 pounds per square inchHardness Rating:80.0 rockwell bMinimum Yield Strength:30000 pounds per square inchSurface Finish:63.0 microinches bearing surface of headMaterial:Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7Surface Treatment:PassivateSurface Treatment Specification:Qu-p-35 federal specification single treatment response	80
Hardness Rating:80.0 rockwell bMinimum Yield Strength:30000 pounds per square inchSurface Finish:63.0 microinches bearing surface of headMaterial:Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7Surface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment response	Min. Tensile Strength (psi):
80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response	80000 pounds per square inch
Minimum Yield Strength:30000 pounds per square inchSurface Finish:63.0 microinches bearing surface of headMaterial:Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7Surface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment response	Hardness Rating:
30000 pounds per square inch Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response	80.0 rockwell b
Surface Finish:63.0 microinches bearing surface of headMaterial:Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7Surface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment response	Minimum Yield Strength:
63.0 microinches bearing surface of head Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response	30000 pounds per square inch
Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response	Surface Finish:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response	63.0 microinches bearing surface of head
Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response	Material:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response	Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Surface Treatment Specification: Qq-p-35 federal specification single treatment response	Surface Treatment:
Qq-p-35 federal specification single treatment response	Passivate
	Surface Treatment Specification:
Thread Series Designator:	Qq-p-35 federal specification single treatment response
	Thread Series Designator:
Unf	Unf
Specification Or Standard:	Specification Or Standard:
6 type	6 type
	Shelf Life:
Shelf Life:	N/a
Shelf Life:	N/a

NSN 5305-00-498-6804

Socket Head Cap Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0