NSN 5305-00-498-7070

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-498-7070 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.189 inches and 0.250 inches **Fastener Length:** Between 0.220 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.112 inches and 0.118 inches **Head Height:** Between 0.070 inches and 0.073 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.073 inches Width Across Flats: Between 0.063 inches and 0.064 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch **Product Name:** Navy special project Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unrc Shelf Life:

N/a

NSN 5305-00-498-7070

Socket Head Cap Screw - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0