

View Online at <https://aerobasegroup.com/nsn/5305-00-499-1316>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.755 inches and 0.822 inches

Fastener Length:

Between 3.203 inches and 3.250 inches

Head Style:

Flat countersunk

Head Diameter:

0.725 inches

Grip Diameter:

Between 0.4982 inches and 0.4991 inches

Single Shear Strength:

18650 pounds per square inch

Internal Drive Style:

Slot

Thread Diameter:

0.500 inches

Grip Length:

Between 2.428 inches and 2.448 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.