NSN 5305-00-499-7694



Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-499-7694 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.341 inches and 0.377 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.494 inches and 0.510 inches **Primary Washer Style:** Flat external teeth

Primary Washer Material Thickness:

Between 0.023 inches and 0.028 inches

Material:

Steel comp 1050 primary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1053 primary washer or steel comp 1054 primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary washer or steel comp 1561 primary washer or steel comp 1566 primary washer

Material Specification:

Sae assn standard all material responses primary washer

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

G-4252m, fscm 24617 mfr ref all treatment responses

Thread Series Designator:

Unc

Shelf Life:

N/a

NSN 5305-00-499-7694

Assembled Washer Screw - Page 2 of 2



		• .					
	In	iŧ	Of	MAG	200		ω.
•	,,,	ıL	v.	IAIC	as	u	┏.

--

Demilitarization:

No

Fiig:

A003b0