NSN 5305-00-500-0398

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-500-0398 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.688 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.102 inches and 0.113 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Primary Washer Outside Diameter:** Between 0.243 inches and 0.257 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.031 inches Material: Steel comp 1010 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener or steel comp 1017 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener **Material Specification:** 66 federal standard all material responses fastener **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification 1st treatment response or qq-z-325, type 1, class 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-500-0398

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0