## NSN 5305-00-500-3519

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-500-3519 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.185 inches and 0.265 inches **Fastener Length:** Between 0.235 inches and 0.265 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Navy special project **Screw Material:** Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1020 **Screw Material Specification:** Qq-s-631 federal specification 1st material response or qq-s-634 federal specification 2nd material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1216 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5305-00-500-3519** Machine Screw - Page 2 of 2



Fiig:

A500d0