# NSN 5305-00-500-3519

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-500-3519



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.185 inches and 0.265 inches

#### Fastener Length:

Between 0.235 inches and 0.265 inches

#### Head Style:

Pan no. 2

Head Diameter:

Between 0.205 inches and 0.219 inches

#### **Head Height:**

Between 0.058 inches and 0.068 inches

#### Internal Drive Style:

High-torque

#### Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Product Name:**

Navy special project

#### Screw Material:

Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1020

#### Screw Material Specification:

Qq-s-631 federal specification 1st material response or qq-s-634 federal specification 2nd material response

#### Screw Surface Treatment:

Passivate

# Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# **Thread Series Designator:**

Unjc

#### **Specification Data:**

80205-nas1216 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

# **NSN 5305-00-500-3519** Machine Screw - Page 2 of 2

Fiig: A500d0

