## NSN 5305-00-501-2719



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-501-2719 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.700 inches and 0.728 inches **Fastener Length:** Between 1.928 inches and 1.958 inches **Head Style:** Oval countersunk **Head Diameter:** 1.018 inches **Shoulder Diameter:** 0.7440 inches first shoulder and 0.7470 inches first shoulder **Shoulder Length:** 0.620 inches first shoulder and 0.650 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 25.0 rockwell c and 31.0 rockwell c **Countersink Angle:** 30.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Thread relief 0.120 in.W by 0.062 in.Radius deep Material: Steel comp 1019 or steel comp 1020 **Surface Treatment:** Phosphate **Thread Series Designator:** Unf Shelf Life: N/a

**Unit Of Measure: Demilitarization:** No

## **NSN 5305-00-501-2719** Shoulder Screw - Page 2 of 2



Fiig:

A003b0