NSN 5305-00-501-9888

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-501-9888 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.318 inches and 0.368 inches **Fastener Length:** Between 0.390 inches and 0.420 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.355 inches and 0.397 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049rjgcams 6322 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:**

N/a

Unjf

Shelf Life:

NSN 5305-00-501-9888

Close Tolerance Screw - Page 2 of 2



	In	i+	∩f	RA.	~~	cii	re:
u	,,,	Iι	vı	IVI	ca.	่อน	ıe.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.