

View Online at <https://aerobasegroup.com/nsn/5305-00-502-5037>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.600 inches

**Fastener Length:**

1.060 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

1.125 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.625 inches

**Thready Qty Per Inch (tpi):**

11

**Countersink Angle:**

70.0 degrees

**Screw Material:**

Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050

**Screw Material Specification:**

Qq-s-630 federal specification 1st material response or qq-s-631 federal specification 2nd material response or qq-s-637 federal specification 2nd material response or qq-s-634 federal specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 7th material response or qq-s-634 federal specification 8th material response or qq-s-634 federal specification 9th material response or qq-s-634 federal specification 10th material response or qq-s-634 federal specification 11th material response or qq-s-634 federal specification 12th material response or qq-s-634 federal specification 13th material response or qq-s-634 federal specification 14th material response or qq-s-634 federal specification 15th material response or qq-s-634 federal specification 16th material response or qq-s-634 federal specification 17th material response or qq-s-634 federal specification 18th material response or qq-s-634 federal specification 19th material response

**Screw Surface Treatment:**

Phosphate

**Special Features:**

Undercut under head 0.490 in. Min 0.500 in. Maximum dia, 0.100 in. Lg

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**