

View Online at <https://aerobasegroup.com/nsn/5305-00-502-5620>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.326 inches

Fastener Length:

Between 0.329 inches and 0.334 inches

Head Style:

Fillister

Head Diameter:

Between 0.734 inches and 0.750 inches

Head Height:

0.187 inches

Internal Drive Style:

Slot

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Screw Material Specification:

Qq-s-630 federal specification 1st material response or qq-s-631 federal specification 2nd material response or qq-s-637 federal specification 2nd material response or qq-s-634 federal specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 7th material response or qq-s-634 federal specification 8th material response or qq-s-634 federal specification 9th material response or qq-s-634 federal specification 10th material response or qq-s-634 federal specification 11th material response or qq-s-634 federal specification 12th material response or qq-s-634 federal specification 13th material response or qq-s-634 federal specification 14th material response or qq-s-634 federal specification 15th material response or qq-s-634 federal specification 16th material response or qq-s-634 federal specification 17th material response or qq-s-634 federal specification 18th material response or qq-s-634 federal specification 19th material response

Screw Surface Treatment:

Phosphate

Special Features:

Undercut under head 0.240 in. Min 0.250 in. Maximum dia, 0.080 in. Lg

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0