

View Online at <https://aerobasegroup.com/nsn/5305-00-502-5620>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.326 inches

**Fastener Length:**

Between 0.329 inches and 0.334 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.734 inches and 0.750 inches

**Head Height:**

0.187 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Screw Material Specification:**

Qq-s-630 federal specification 1st material response or qq-s-631 federal specification 2nd material response or qq-s-637 federal specification 2nd material response or qq-s-634 federal specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 7th material response or qq-s-634 federal specification 8th material response or qq-s-634 federal specification 9th material response or qq-s-634 federal specification 10th material response or qq-s-634 federal specification 11th material response or qq-s-634 federal specification 12th material response or qq-s-634 federal specification 13th material response or qq-s-634 federal specification 14th material response or qq-s-634 federal specification 15th material response or qq-s-634 federal specification 16th material response or qq-s-634 federal specification 17th material response or qq-s-634 federal specification 18th material response or qq-s-634 federal specification 19th material response

**Screw Surface Treatment:**

Phosphate

**Special Features:**

Undercut under head 0.240 in. Min 0.250 in. Maximum dia, 0.080 in. Lg

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0