NSN 5305-00-503-5689

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-503-5689

Thread Class:
3a Thread Direction:
Right-hand
Thread Length:
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 0.823 inches and 0.853 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No

NSN 5305-00-503-5689

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

