## NSN 5305-00-505-2930

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-505-2930 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 1.011 inches and 1.041 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: se

Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment respons
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No

## NSN 5305-00-505-2930

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0