## NSN 5305-00-505-3300

Close Tolerance Screw - Page 1 of 2



Group

View Online at https://aerobasegroup.com/nsn/5305-00-505-3300

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.350 inches and 0.400 inches
Fastener Length:
Between 0.672 inches and 0.702 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.429 inches and 0.477 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.312 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp e4340 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Νο

## NSN 5305-00-505-3300

Close Tolerance Screw - Page 2 of 2

**Fiig:** A003b0

