NSN 5305-00-505-3356

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-505-3356 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.318 inches and 0.368 inches **Fastener Length:** Between 0.453 inches and 0.483 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.355 inches and 0.397 inches **Grip Diameter:** Between 0.2485 inches and 0.3495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-00-505-3356

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0