NSN 5305-00-505-3441

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-505-3441



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.318 inches and 0.368 inches
Fastener Length:
Between 0.453 inches and 0.483 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.266 inches and 0.303 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unif
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-00-505-3441

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

