NSN 5305-00-505-3458

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-505-3458

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.318 inches and 0.368 inches
Fastener Length:
Between 0.578 inches and 0.608 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.355 inches and 0.397 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
Between 0.240 inches and 0.260 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-00-505-3458

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

