## NSN 5305-00-505-4070

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-505-4070 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.318 inches and 0.368 inches **Fastener Length:** Between 0.390 inches and 0.420 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.266 inches and 0.303 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-00-505-4070

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0