Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-507-8314



## **Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.619 inches and 0.722 inches Fastener Length: Between 0.719 inches and 0.750 inches **Head Style:** Hexagon **Head Height:** Between 0.173 inches and 0.183 inches Width Between Flats: Between 0.428 inches and 0.437 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Primary Washer Outside Diameter:** Between 0.466 inches and 0.478 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** Between 0.023 inches and 0.028 inches Material: Steel comp 1010 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener or steel comp 1017 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener **Material Specification:** 66 federal standard all material responses primary washer Surface Treatment: Cadmium or zinc **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

1

---

## NSN 5305-00-507-8314

Assembled Washer Screw - Page 2 of 2

**Fiig:** A003b0

