## NSN 5305-00-508-2718

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-508-2718 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.288 inches and 0.348 inches **Fastener Length:** Between 0.953 inches and 0.983 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.266 inches and 0.286 inches **Shoulder Diameter:** 0.193 inches first shoulder and 0.195 inches first shoulder **Shoulder Length:** 0.595 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 33.0 rockwell c and 37.0 rockwell c **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** 2 thds tapered Material: Steel comp 4037 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-508-2718

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0