NSN 5305-00-508-3048

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-508-3048

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 0.386 inches and 0.416 inches
Head Style:
Pan
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.105 inches and 0.115 inches
Grip Diameter:
Between 0.1625 inches and 0.1635 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.164 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Product Name:
Navy special project
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-00-508-3048

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

