NSN 5305-00-508-3086

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-508-3086

| - | |
|--------------|--|
| Thread Clas | SS: |
| 3a | |
| Thread Dire | ection: |
| Right-hand | |
| Thread Len | - |
| | 251 inches and 0.301 inches |
| Fastener Le | |
| | 073 inches and 2.103 inches |
| Head Style: | : |
| Pan | |
| Head Diam | |
| | 357 inches and 0.373 inches |
| Head Heigh | |
| | 122 inches and 0.133 inches |
| Grip Diame | |
| | 1885 inches and 0.1895 inches |
| Internal Dri | - |
| Cross reces | |
| Thread Dia | |
| 0.190 inche | |
| Grip Lengtl | |
| | 802 inches and 1.822 inches |
| Thready Qt | y Per Inch (tpi): |
| 32 | |
| | e Strength (psi): |
| - | inds per square inch |
| Surface Fin | |
| | nches threads |
| Product Na | |
| Navy specia | al project |
| Material: | |
| | oy uns r54520 |
| - | pecification: |
| | mp 6al-4v assn standard single material response |
| | ies Designator: |
| Unjf | |
| Shelf Life: | |
| N/a | |
| Unit Of Mea | asure: |
| | |
| Demilitariza | ation: |
| No | |

NSN 5305-00-508-3086

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

