## NSN 5305-00-508-4230

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-508-4230 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 0.386 inches and 0.416 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads **Product Name:** Navy special project Material: Titanium alloy uns r54520 **Material Specification:** Nas621, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1083 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-508-4230

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0