NSN 5305-00-508-5149

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-508-5149 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.291 inches and 0.341 inches Fastener Length: Between 0.989 inches and 1.019 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.456 inches and 0.508 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** se

Surface Treatment Specification.
Qq-p-35 federal specification single treatment respons
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

NSN 5305-00-508-5149

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0