NSN 5305-00-508-6201

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-508-6201 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.136 inches and 0.176 inches **Fastener Length:** Between 0.406 inches and 0.438 inches **Head Style:** Round **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.071 inches and 0.081 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.230 inches and 0.302 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 **Material Specification:** Qq-s-763 federal specification 1st material response or astm a582 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-508-6201

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.