NSN 5305-00-508-6353

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-508-6353 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 0.699 inches and 0.729 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.296 inches and 0.331 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-508-6353

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0