## NSN 5305-00-508-6921

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-508-6921 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 0.386 inches and 0.416 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.246 inches and 0.280 inches **Grip Diameter:** Between 0.1365 inches and 0.1375 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.138 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-508-6921

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0