

View Online at <https://aerobasegroup.com/nsn/5305-00-510-6547>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.542 inches and 0.665 inches

Fastener Length:

Between 1.010 inches and 1.030 inches

Head Style:

Double hexagon w/hole

Head Height:

0.388 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

0.091 inches

Thread Diameter:

0.375 inches

Features Provided:

Unfinished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-8503 military specification 4th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.